

FC København

Specifications perimeter

Full length: 19200x90 pixels
Center board: 1000x90 pixels

Final export resolution: See examples to the right

Duration: 30 sec. Frame rate: 30 fps

Color mode: RGB (8 or 16 bit)

File format and Codec: MOV Animation / MOV H.264 / MP4 H.264

File compression: ZIP (.zip)

Instructions

Tiling

Standard export resolutions will automatically be tiled over the entire length of the LED perimeter display.

If center board is required the full perimeter export must be line wrapped in a 1920x1080 pixel canvas as demonstrated to the right.

Producing the animation

Create the perimeter animation according to the pixel dimensions shown to the right.

Exporting the animation

Export the animation according to the specifications shown above.

Export resolutions

Tiling (only an obtion without center board) 600x90 pixels (1/32) expromo 800x90 pixels (1/24) Bright in every way. (expromo) 1200x90 pixels (1/16) EXPROMO Bright in every way. EXPROMO 2400x90 pixels (1/8) (expromo) Bright in every way. (expromo) (expromo) Bright in e 4800x90 pixels (1/4) (EXPROMO) Bright in every way. (EXPROMO) (EXPROMO) Bright in e Full length (required with center board) Final export layout (canvas 1920x1080 pixels) (EXPROMO) Bright in every way. (EXPROMO) Bright in every way. (EXDIOMO) Bright in every way. (EXDIOMO D) Bright in every way. (EXDIOMO) Bright in every way. EXPROMO) Bright in every way. (EXPROMO) Bright in ex rery way. (ヒメロイロの) Bright in every way. **SUPI** (EXPROMO) Bright in every way. (EXPR RLIGA DMO) Bright in every way. (EXDCOMO) Bright in every way (expromo) Bright in every way. (expromo) Bright in every way. (EXDIOMO) Bright in every way. (EXDIOM no) Bright in every way. (expromo) Bright in every way.